

- 1. ALL POSTS SHALL BE W6 X 9 AS SHOWN ON STANDARD MD 605.23.
- 2. WOOD OFFSET BLOCKS SHALL BE AS SHOWN ON STANDARD MD 605.21.
- 3. THE TRAFFIC BARRIER W-BEAM SECTIONS SHALL BE LAPPED IN THE DIRECTION OF TRAFFIC.
- 4. MAY SPAN 5'. 10' & 15' COG OR COS INLETS. LOW FILL BOX CULVERT OR OTHER OBJECT WHICH INTERFERS WITH NORMAL PLACEMENT OF POST.
- 5. THE SPLICE ON BOTH RAILS MUST BE COINCIDENT.

SPECIFICATION CATEGORY CODE ITEMS

	605			
	APPROVED	Kil 6. M°CILL  DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT		STATE HIGHWAY ADMINISTRATION STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES TRAFFIC BARRIER W BEAM
	SXA	APPROVAL • SHA REVISIONS  APPROVAL 11-10-99  REVISED 10-1-01	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION APPROVAL 7-2-97 REVISED 7-2-99	
	CI TTO 1Drive to Block	REVISED REVISED	REVISED REVISED	STANDARD NO. MD 605.26
				LOF 2

**Maryland Department of Transportation**